


Philips
S-video to scart cable

5.0 m

SWV6624



Enjoy the ultimate viewing experience

with this premium video cable

Take your components to optimum performance. This top of the line cable offers the best connection for transferring video signals between components.

Enjoy better picture quality

- 24 carat gold-plated connectors optimize signal
- 99.97% Oxygen-Free Copper (OFC)

Protects against signal loss

- 100% aluminum shielding
- Oxygen-free copper conductor for ideal signal transfer
- Copper braided shielding

Easy installation

- Color coded connectors for instant recognition
- Non-slip ergonomic grip for easy use
- Plug and play for easy use

Enjoy extended durability

- Heavy-duty brass shell for extended durability
- Super pliable jackets for outstanding flexibility
- Reliable metal strain relief

PHILIPS
sense and simplicity

S-video to scart cable
5.0 m

Specifications

Inner Carton

- EAN/UPC/GTIN: 87 10895 99403 3
- Quantity: 2
- Gross weight: 1.32 kg
- Tare weight: .18 kg
- Net weight: 1.14 kg
- Length (cm): 31.5 cm
- Width (cm): 15 cm
- Height (cm): 21 cm

Outer Carton

- EAN/UPC/GTIN: 87 10895 99404 0
- Quantity: 4
- Gross weight: 3.24 kg
- Tare weight: .6 kg

- Net weight: 2.64 kg
- Length (cm): 33 cm
- Width (cm): 32.5 cm
- Height (cm): 23.5 cm

Packaging

- EAN/UPC/GTIN: 87 10895 99402 6
- Quantity: 1
- Gross Weight: .56 kg
- Tare Weight: .1 kg
- Net Weight: .46 kg
- Height: 9 cm
- Length: 28.5 cm
- Width: 20 cm

SWV6624/I0

Product highlights

24 carat gold-plated connector

24 carat gold-plated connectors ensure the best signal quality for your components.

99.97% OFC solid conductor

99.97% Oxygen-free copper (OFC) cable core provides optimum signal quality.

100% aluminum shielding

This protective layer of aluminum guards against electromagnetic interference for improved signal quality.

Solid high purity OFC

This oxygen-free copper conductor provides the highest accuracy in signal transfer with minimal resistance.

Copper braided shielding

This protective layer of copper blocks radio frequency interference for improved signal quality.

Color-coded connectors

Color coded connections make it easy to install your cable into the correct inputs and outputs

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

Plug and play

Plug and play offers easy installation of components without time-consuming installations.

Heavy-duty brass shell

The heavy-duty brass shell protects the internal connection of the cable. It ensures durability and the reliability of your connection.

Super pliable jackets

Super pliable PVC jackets are abrasion-resistant for outstanding flexibility and protection against everyday wear and tear.

Metal strain relief

Full metal connector ensures extended durability by preventing damage during use and installation.



Issue date 2008-03-13

Version: 1.0.3

12 NC: 9082 100 09767
EAN: 87 10895 99402 6

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com